




# STANDARDS FOR GAS APPLICATIONS

## PRODUCTS FOR GAS APPLICATIONS; STD + XS + 0.625" + 0.750" + 1.000"

	Material	Standard	2" 60	3" 89	4" 114	6" 168	8" 219	10" 273	12" 324	14" 355	16" 408	18" 457	20" 508	24" 610	28" 711	30" 762	36" 914	42" 1067	
	WPB	ASME B 16.9																	LR/R=3D
	WPL6	ASME B 16.9																	LR/R=3D
	CSA 359	CSA Z245.11																	LR/R=3D
	WPHY-42	MSS SP-75																	LR/R=3D
	WPHY-52	MSS SP-75																	LR/R=3D
	WPHY-60	MSS SP-75																	LR/R=3D
	WPHY-65	MSS SP-75																	LR/R=3D
	WPHY-70	MSS SP-75																	LR/R=3D
	WPB	ASME B 16.9																	equal a. red.
	WPL6	ASME B 16.9																	equal a. red.
	CSA 359	CSA Z245.11																	equal a. red.
	WPHY-42	MSS SP-75																	equal a. red.
	WPHY-52	MSS SP-75																	equal a. red.
	WPHY-60	MSS SP-75																	equal a. red.
	WPHY-65	MSS SP-75																	equal a. red.
		WPB	ASME B 16.9																
WPL6		ASME B 16.9																	conc. a. exc.
CSA 359		CSA Z245.11																	conc. a. exc.
WPHY-42		MSS SP-75																	conc. a. exc.
WPHY-52		MSS SP-75																	conc. a. exc.
WPHY-60		MSS SP-75																	conc. a. exc.
WPHY-65		MSS SP-75																	conc. a. exc.